

16 December 2024

**REQUEST FOR QUOTATION**

The **TOURISM PROMOTIONS BOARD** invites you to submit quotation for the item/s listed below:

**RFQ No.** TPB RFQ 2024-12-362  
**PR No.** 12.005  
**Requirements:** SUPPLY AND DELIVERY OF VIDEO CAMERA AND DSLR

Quantity	Item/Description	Estimated Unit Price	Total Cost (Php)
1 Lot	<p><b>SUPPLY AND DELIVERY OF VIDEO CAMERA AND DSLR</b></p> <p><b>SCOPE OF WORK/SERVICES/DELIVERABLES</b></p> <p><b>a. 1 unit VIDEO CAMERA</b></p> <ul style="list-style-type: none"> <li>i. Sensor Type: 12.1MP Full-frame (35.6 x 23.8mm) Exmor R CMOS</li> <li>ii. Effective Resolution: 12.1 megapixels</li> <li>iii. Processor: BIONZ XR ISO Range</li> <li>iv. Standard: 80–102,400</li> <li>v. Expanded: 40–409,600</li> <li>vi. Autofocus Type: Fast Hybrid AF</li> <li>vii. AF Points: 759 phase-detection points (92% coverage)</li> <li>viii. Eye AF: Real-time Eye AF for humans and animals</li> <li>ix. Touch Tracking: Yes</li> <li>x. Image Stabilization Type: 5-axis in-body image stabilization (IBIS) Effectiveness: Up to 5.5 stops of compensation</li> <li>xi. Active Mode: Digital stabilization for video</li> <li>xii. Video Recording 4K (3840 x 2160): Up to 120fps</li> <li>xiii. Full HD (1080p): Up to 240fps</li> <li>xiv. Bit Depth: 10-bit 4:2:2 internal recording</li> <li>xv. Formats: XAVC HS (HEVC/H.265), XAVC S, and XAVC S-I</li> <li>xvi. Color Profiles: S-Log3, S-Gamut3.Cine, HLG (Hybrid Log-Gamma)</li> <li>xvii. Dynamic Range: 15+ stops</li> <li>xviii. Viewfinder Type: OLED electronic viewfinder (EVF)</li> <li>xix. Resolution: 9.44 million dots</li> <li>xx. Magnification: 0.91x</li> <li>xx. Refresh Rate: 120Hz LCD</li> <li>xxi. Monitor Size: 3.0 inches</li> <li>xxii. Resolution: 1.44 million dots</li> <li>xxiii. Type: Vari-angle touchscreen LCD</li> <li>xxiv. Touch Functionality: Yes</li> <li>xxv. Storage Slots: Dual card slots supporting CFexpress Type A and SD UHS-II Burst Shooting</li> <li>xxvi. Continuous Shooting: Up to 10fps with AF/AE tracking Build</li> <li>xxvii. Dimensions Material: Magnesium alloy, dust and moisture-resistant</li> <li>xxviii. Dimensions: 129.9 x 96.9 x 80.8mm (5.12 x 3.82 x 3.18 inches)</li> </ul>	Php 250,000.00	Php 740,000.00

	<p>xxix. Weight: Approx. 699g (1.54 lbs) with battery and memory card</p> <p>xxx. Battery Type: NP-FZ100 Life: Approx. 510 shots (LCD), 600 shots (viewfinder), or up to 135 mins of continuous video recording</p> <p>xxxi. Connectivity Ports: Full-size HDMI, USB-C 3.2 Gen 1, Micro-USB, headphone and microphone jacks, multi-interface shoe</p> <p>xxxii. Wireless: Wi-Fi (2.4 GHz &amp; 5 GHz), Bluetooth 5.0, FTP file transfer</p> <p>xxxiii. Additional Features Timecode Sync: Yes, for multi-camera setups</p> <p>xxxiv. Heat Management: Improved design for extended 4K recording</p> <p><b>b. 1 unit LENS</b></p> <p>i. Focal Length: 24-70mm Maximum Aperture: f/2.8</p> <p>ii. Minimum Aperture: f/22</p> <p>iii. Lens Construction: 20 elements in 15 groups Includes 5 aspherical elements, 2 extra-low dispersion (ED) elements, 2 Super ED elements, and 2 XA (extreme aspherical) elements for high resolution and minimal distortion Nano AR Coating II to reduce ghosting and flare Aperture</p> <p>iv. Aperture Blades: 11 rounded blades for smooth, pleasing bokeh</p> <p>v. Aperture Range: Constant f/2.8 across the zoom range</p> <p>vi. Autofocus Focus System: Four XD (Extreme Dynamic) Linear Motors for fast, precise, and quiet AF</p> <p>vii. Minimum Focusing Distance: 0.21m (8.3 inches) at 24mm, 0.30m (11.8 inches) at 70mm</p> <p>viii. Maximum Magnification: 0.32x Size &amp; Weight Length: 119.9mm (4.72 inches)</p> <p>ix. Diameter: 87.8mm (3.46 inches)</p> <p>x. Weight: Approx. 695g (1.53 lbs), significantly lighter than the first-generation model</p> <p>xi. Build Quality Mount: Sony E-mount, full-frame compatible</p> <p>xii. Construction: Dust and moisture-resistant design for rugged outdoor use</p> <p>xiii. Front Element: Fluorine coating to resist fingerprints, dust, and moisture Control &amp; Handling</p> <p>xiv. Zoom Mechanism: Internal zoom (lens does not extend)</p> <p>xv. Zoom Ring: Smooth, variable torque zoom ring for better control</p> <p>xvi. Focus Ring: Linear Response MF for intuitive manual focus control</p> <p>xvii. Customizable Buttons: Two focus hold buttons on the barrel</p> <p>xviii. Aperture Ring: Clickable and de-clickable aperture ring for video and photo versatility</p> <p>xix. Zoom Smoothness Switch: Adjust zoom ring torque for a smoother or tighter feel</p> <p>xx. Compatibility Filter Thread: 82mm</p>	<p>PHP 145,000.00</p>	
--	--	-----------------------	--

	<p>xxi. Compatibility: Full-frame Sony E-mount cameras (also compatible with APS-C models with an effective focal range of 36-105mm)</p> <p><b>c. 1 unit DSLR</b></p> <p>i. Sensor &amp; Processor Sensor: 45MP full-frame (36 x 24mm) CMOS sensor</p> <p>ii. Processor: DIGIC X ISO</p> <p>iii. Range Standard: 100–51,200 Expanded: 50–102,400</p> <p>iv. Autofocus AF System: Dual Pixel CMOS AF II</p> <p>v. AF Points: 1,053 automatically selected AF points</p> <p>vi. Focus Modes: Eye Detection AF, Animal Detection AF, Human Detection</p> <p>vii. AF Coverage: 100% vertical and horizontal coverage in</p> <p>viii. AF mode Low-Light Sensitivity: Up to -6</p> <p>ix. EV Image Stabilization Type: In-body 5-axis image stabilization (IBIS)</p> <p>x. Effectiveness: Up to 8 stops of correction with compatible lenses</p> <p>xi. Video Recording 8K (8192 x 4320): Up to 30fps, 12-bit</p> <p>xii. RAW internal recording 4K (3840 x 2160): Up to 120fps 10-bit</p> <p>xiii. Internal Recording: Yes, with 4:2:2 color sampling</p> <p>xiv. Formats: RAW, H.265 (HEVC), and H.264 HDR: HDR PQ (Perceptual Quantization) for HDR workflows</p> <p>xv. Log Profiles: Canon Log for wider dynamic range</p> <p>xvi. Burst Shooting Mechanical Shutter: Up to 12fps</p> <p>xvii. Electronic Shutter: Up to 20fps</p> <p>xviii. Viewfinder Type: OLED electronic viewfinder (EVF) Resolution: 5.76 million dots</p> <p>xix. Magnification: 0.76x Refresh Rate: 120Hz</p> <p>xx. LCD Monitor Size: 3.2 inches Resolution: 2.1 million dots</p> <p>xxi. Type: Vari-angle touchscreen</p> <p>xxii. LCD Touch Functionality: Yes</p> <p>xxiii. Storage Card Slots: Dual card slots 1x CFexpress Type B 1x SD UHS-II</p> <p>xxiv. Build &amp; Dimensions Material: Magnesium alloy, weather-sealed construction</p> <p>xxv. Dimensions: 138 x 97.5 x 88mm (5.43 x 3.84 x 3.46 inches)</p> <p>xxvi. Weight: Approx. 738g (1.63 lbs) with battery and memory card</p> <p>xxvii. Battery Type: LP-E6NH (also compatible with LP-E6N and LP-E6 batteries)</p> <p>xxviii. Life: Approx. 320 shots per charge with the EVF, 490 shots with the LCD (CIPA rating)</p> <p>xxix. Connectivity Ports: Microphone, headphone, HDMI (Type D), USB-C, flash sync</p> <p>xxx. Wireless: Wi-Fi (5GHz and 2.4GHz), Bluetooth 5.0</p> <p>xxxi. Additional Features Time-lapse: 8K time-lapse capability</p> <p>xxxii. Weather-Sealed: Yes, suitable for professional use in various environments</p> <p>xxxiii. Compatibility: RF mount lenses (also compatible with EF lenses via adapter)</p>	PhP240,000.00	
--	---	---------------	--

	<p>xxxiv. Heat Management: Overheat control for extended video recording</p> <p><b>d. 1 unit LENS</b></p> <ul style="list-style-type: none"> <li>i. Focal Length: 24-105mm Maximum Aperture: f/4</li> <li>ii. Minimum Aperture: f/22 Lens Construction: 18 elements in 14 groups Includes 3 aspherical elements and 1 UD (Ultra-Low Dispersion) element to reduce chromatic aberrations and maintain sharpness</li> <li>iii. Aperture Aperture Blades: 9 rounded blades for smooth bokeh</li> <li>iv. Aperture Range: Constant f/4 across the zoom range Image</li> <li>v. Stabilization Type: Optical Image</li> <li>vi. Stabilization Effectiveness: Up to 5 stops of stabilization, ideal for handheld shooting Autofocus AF System: Nano USM (Ultra Sonic Motor) for fast, quiet, and smooth AF, suitable for both photography and video</li> <li>vii. Focus Control: Full-time manual focus override available Minimum</li> <li>viii. Focusing Distance Distance: 0.45m (17.7 inches)</li> <li>ix. Maximum Magnification: 0.24x Size &amp; Weight Length: 107.3mm (4.22 inches) <ul style="list-style-type: none"> <li>x. Diameter: 83.5mm (3.29 inches)</li> <li>xi. Weight: Approx. 700g (1.54 lbs)</li> </ul> </li> <li>xii. Build Quality Mount: Canon RF-mount, full-frame compatible</li> <li>xiii. Construction: Weather-sealed design for dust and moisture resistance</li> <li>xiv. Front Element: Fluorine coating to resist fingerprints, dust, and moisture</li> <li>xv. Control &amp; Handling</li> <li>xvi. Zoom Mechanism: Extending zoom (lens length changes when zooming)</li> <li>xvii. Control Ring: Customizable control ring on the lens for adjusting settings like ISO, shutter speed, or aperture</li> <li>xviii. Compatibility Filter Thread: 77mm</li> <li>xix. Compatibility: Designed for Canon RF-mount cameras (e.g., EOS R, R5, R6)</li> <li>xx. Additional Features Focus Ring: Smooth, electronic focus control for precise manual focus Versatility: Ideal focal length range for general-purpose photography (landscapes, portraits, travel, etc.)</li> </ul> <p><b>DELIVERY PERIOD:</b> Must be delivered within thirty (30) calendar days upon receipt of Notice to Proceed (NTP) after which liquidated damages shall be imposed.</p> <p><b>ADDITIONAL TECHNICAL/ELIGIBILITY REQUIREMENTS:</b></p> <ol style="list-style-type: none"> <li>1. Company Profile</li> <li>2. Accomplished Statement of Compliance to the Technical Specification Annex "A"</li> <li>3. SEC/DTI Certificate of Registration</li> <li>4. Must be a Company operating for at least three (3) years.</li> </ol>	<p>PhP105,000.00</p>	
--	---	----------------------	--

	<p>5. Must be certified reseller of the product offered. 6. Provide brochures or images of the proposed product.</p> <p><b>LEGAL REQUIREMENTS:</b></p> <ol style="list-style-type: none"> <li>1. PhilGEPS Registration Certificate</li> <li>2. Business/Mayor's Permit</li> <li>3. Business/ Income Tax Return Certificate</li> <li>4. Notarized Omnibus Sworn Statement</li> </ol> <p><b>ATTACHMENTS:</b></p> <ol style="list-style-type: none"> <li>1. Technical Specifications</li> <li>2. Statement of Compliance</li> </ol> <p><b>NOTE:</b></p> <ol style="list-style-type: none"> <li>1. All entries must be typewritten in your company letterhead.</li> <li>2. Price validity shall be for a period of thirty (30) calendar days.</li> </ol>		
Terms	30 calendar days upon receipt of invoice		
ABC	PhP740,000.00 inclusive of all applicable fees and taxes		<b>PhP740,000.00</b>

Please submit your **quotation and legal** documents duly signed by your authorized representative to email address [kristine\\_aclan@tpb.gov.ph](mailto:kristine_aclan@tpb.gov.ph)/ [bac\\_sec@tpb.gov.ph](mailto:bac_sec@tpb.gov.ph) or to the office address **6/F, Five E-Com Center, Harbor Drive, Mall of Asia Complex, Pasay City**, not later than **20 December 2024 at 5:00 PM**, subject to the Terms and Conditions stated herein.

Please be informed that the Tourism Promotions Board is evaluating our suppliers' performance based on these criteria: Quality (40%), Cost (25%), Timeliness (25%), and Customer Service (10%).

Thank you very much.



**JANET G. VILLARRANCA**  
Officer-in-Charge  
Procurement Management Division

**Contact person: Kristine Heizelle B. Aclan**